



Previous Name: **Shell Donax TC 30**

# Shell Spirax S4 CX 30

## *High Performance Off-Highway Transmission and Hydraulic Oil for Many Applications*

Shell Spirax S4 CX 30 is designed to provide operators with trouble free operation and maximum reliability for the lifetime of the equipment. Spirax S4 CX meets the demanding requirements of modern transmission, final drive, oil immersed brake and hydraulic systems fitted to heavy-duty off-highway.

### Applications

Spirax S4 CX 30 is recommended for use heavy duty off-highway equipment produced by the world's leading manufactures including; Caterpillar, Komatsu, Komatsu-Dresser and in transmissions manufactured by Eaton, Eaton Fuller, ZF, Dana, Rockwell amongst other:

- Powershift Transmissions
- Final drives
- Oil immersed brakes
- Hydraulic systems

### Performance Features and Benefits

- **Frictional performance and material compatibility**  
Highly consistent and reliable friction performance when used with the advanced metallic and non-metallic materials found in modern systems. Minimal clutch slippage, smooth and quiet brake operation, and trouble-free transmission operation.
- **Anti-wear protection**  
The shear-stable SAE 30 viscosity grade is free from viscosity index (VI) improvers and thickeners and give the best protection of heavily loaded components.
- **Low temperature characteristics**  
Formulated to meet low temperature viscosity and fluidity requirements, providing superior protection during start-up and low operating temperature conditions.
- **Optimum mechanical performance and long oil life**  
Wide-ranging protection for critical components, such as bronze friction discs in powershift transmissions and gears in final drives and differential units.

- **Vickers 35V25 hydraulic pump test**  
Excellent performance in this demanding test.

- **Oxidation stability**  
Contains inhibitors to control oxidation and deposit formation. Protects both ferrous and non-ferrous metals from corrosion. Suppresses foaming with improved flow properties at low temperatures enhances efficiency.

### Specification and Approvals

Spirax S4 CX 30 is suitable for use where the following specifications are called for:

Caterpillar Tractor - TO-4  
ZF - TE-ML 03C, 07F

*Suitable for use in applications where Allison C-4 type fluids are required*

*Spirax S4 CX 30 oil is suitable for use in many powershift or manual transmissions, wet brake systems, and some hydraulic systems including Komatsu.*

### Advice

Advice on applications not covered in this leaflet may be obtained from your Shell Representative.

### Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Shell representative.

### Protect the environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water



## Typical Physical Characteristics

Spirax S4 CX 30			
SAE Viscosity grade		SAE J 300	30
Kinematic Viscosity		ISO 3104	
at 40°C	mm <sup>2</sup> /s		93.9
at 100°C	mm <sup>2</sup> /s		10.9
Density at 15°C	kg/m <sup>3</sup>	ISO 12185	899
Flash Point COC	°C	ISO 2592	205
Pour Point	°C	ISO 3016	-30

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.